


100BN43.7-51 380-415V
Technical specification
3~ 50 Hz

Pump

Series	BN
Pump name	100BN43.7-51 380-415V
Standard	N/A

Motor data

Motor	CT1-4-4-U D
Rated voltage	380 V
Frequency	50 Hz
Motor phases	3~
Number of poles	4
Rated power P_2	3.70 kW
Rated current	8.4 A
rpm	1411 1/min
Rated torque	25.0 Nm
Start*	Direct starting

Degree of protection	IP 68
Insulation class	F
Protection device	Circle thermal protector
Type of oil	Turbine oil VG32
Oil amount	1.25 l

Hydraulic

Free passage	
Impeller type	Channel impeller with Cutting mechanism
Max. hydraulic efficiency	61.2 %
Discharge	100 mm
Curve tolerance	UNI EN ISO 9906:2012

Operating limits (standard pumps)

Max. liquid temperature	40 °C
Max. density treated liquid	1030 kg/m ³
pH treated liquid	5-9
Max. start per hour (equally distributed)	6
Wet/dry use	WET
Operating mode	S1

Construction materials

Motor enclosure	Gray Iron Casting 200
Shaft	420J2 Stainless Steel
Pump Casing	Gray Iron Casting 250
Impeller	Ductile Iron Casting 500
Suction Cover	Ductile Iron Casting 500
Suction plate	N/A
Painting	Epoxy paint (Black)
Screws	304 Stainless Steel
Gaskets	NBR

Construction features

Power cable1	4C*2mm ²
Power cable2	N/A
Sheath	VCT
Control cable	N/A
Sheath	N/A
Cable length*	6 m
Mechanical seals	H-35A
Weight**	92 kg

* Please inquire about cable extensions
 ** cable's weight not included

Monitoring features


Monitoring option	
leaking sensor -	N/A
monitoring equipment -	N/A

100BN43.7-51 380-415V

Pump performance curves

3 ~ 50 Hz

Discharge	Head	Capacity	Rated power	Voltage	Current	rpm
100 mm			3.7 kW	380 V	8.4 A	1411 1/min





Characteristic curves according to UNI EN 9906:2012 for pumps with standard material combination
P2<10kW: paragraph 4.4.2
10kW<P2<100kW: Grade 3B
P2>100kW: Grade 2B

DIMENSION DRAWING		No.	No.	A-31960-15
TYPE	Submersible Sewage & Wastewater Pump	MODEL	100BN43.7 -51	


Approximate Weight(※)
92kg

※excluding cable



C.W.L.:Continuous running Water Level
L.W.L.:Lowest running Water Level

SECTIONAL DRAWING			No.		No.	A-31967-15
TYPE	Submersible Sewage & Wastewater Pump			MODEL	100BN43.7 -51	



REQ. SPECIFICATION

No.	DESCRIPTION	Q'TY	MATERIAL / NOTE	No.	DESCRIPTION	Q'TY	MATERIAL / NOTE
1	Cabtyre Cable	1	PVC Sheath	48	Screwed Flange	1	Gray Iron Casting 200
20	Pump Casing	1	Gray Iron Casting 250	50	Motor BrackEt	1	Gray Iron Casting 200
21	Impeller	1	Ductile Iron Casting 500	52A	Upper Bearing	1	6304ZZC3
22	Suction Cover	1	Ductile Iron Casting 500	52B	Lower Bearing	1	6309ZZC3
23	Stand	3	Steel Plate	53	Motor Protector	1	
25	Mechanical Seal	1	H-35A	54	Shaft	1	420J2 Stainless Steel
26	Oil Seal	1	TC507212	55	Rotor	1	
29	Oil Casing	1	Gray Iron Casting 250	56	Stator	1	
30	Oil Lifter	1	Plastic	35	Bearing Housing	1	Gray Iron Casting 200
60	Oil Plug	1	304 Stainless Steel	64	Motor Frame	1	Gray Iron Casting 200
36	Lubricant		Turbine Oil(ISO VG32)	72	Eyebolt	2	304 Stainless Steel
37	Discharge Bend	1	Gray Iron Casting 200				
46	Air Release Valve	1	Nylon				